

FEATURE

- Multiple range for selection (X1 X10 X100), Max :1200Ω
- For precise 3-pole earth resistance measurement or simplify 2-pole earth resistance measurement.
- Capable of measuring earth voltage, Max: AC 30V
- "AUX. SPIKE OK" Light indication for correct 3-pole earth resistance measurement
- Output rated current:3mA max.
- Taut Band movement
- Lighting function for reading at dim spots
- Low battery indication
- Design meets IEC 61010-1 CAT III 300V, IEC 61557 & IEC 61010-031 safety standard.



SPECIFICATION

| | |
|-----------------------|---|
| Measurement Ranges | Earth Resistance: 0-12Ω/0-120Ω/0-1200Ω Earth Voltage: AC 0-30V (50/60Hz) |
| Accuracy | Earth Resistance: ±3% of full scale Earth Voltage: ±3% of full scale |
| Overload Protection | Earth Resistance: AC 276V for 10 seconds Earth Voltage: AC 276V for 1 minute |
| Safety Standards | IEC 61010-1 CAT III 300V · IEC 61557 · IEC 61010-031 |
| Insulation Resistance | >=100MΩ/DC1000V |
| Withstand Voltage | AC3700V for 1 minute |
| Dimensions | 162(L)x112(W)x50(H)mm(6.4"x4.4"x2.0") |
| Power Source | R6P(AA) 1.5Vx4 |
| Weight | Approx. 400g(exclude Battery) |

得益工業儀器有限公司

DER EE

ELECTRICAL INSTRUMENT CO., LTD.

台灣 新北市中和區中山路二段351號7F
7F, No. 351, Sec. 2, Chung Shan Rd.,
Chung Ho Dist., New Taipei City, Taiwan
TEL:886-2-2226-6789(REP) FAX:886-2-2226-7979
E-mail:deree@ms21.hinet.net
<http://www.deree.com.tw>

Specifications and appearance may be revised if needed without any prior notice. Any further product info, please contact us.