

Low Loss Serial Digital Coaxial

Type: RG-6/U

Applications

Coaxial Cable for Communication, Audio, Video, CCTV, CATV, MATV, Broadband, or Broadcast. Precision Video Cable for Analog and Digital, Low Loss Serial Digital Coaxial, video Cable, Precision Video Cables for Analog and Digital Applications, RG-6/U Type

Standards

All Odeskabel CATV coaxial cables comply with the European standard and safety standards. The products are designed according to the international standard IEC 1196 for Radio Frequency cables and the European standard EN50117.

Construction

1) CONDUCTOR:

Number of Coax: 1

Total Number of Conductors: 1

AWG: 18

Stranding: Solid

Conductor Diameter: 0.040 in.

Conductor Material: BC - Bare Copper

2) INSULATION:

Insulation Material: Gas-injected FHDPE - Foam High

Density Polyethylene

Insulation Diameter: 0.180 in.

OUTER SHIELD:

Outer Shield Material: Tape/Braid

Outer Shield Material % Coverage (%):

3) TAPE - Aluminum Foil/Polyester Tape/Aluminum Foil (100 %)

4) BRAIDE - TC - Tinned Copper (95 %)

5) OUTER JACKET:

Outer Jacket Material: PVC - Polyvinyl Chloride, FR, PVC or LSZH, PE

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter: 0.274 in.

