

Bench Type



CE

ED-205

- **Dimension** : 91(L) × 103(W) × 100(D)mm
- **Deflection Angle** : 90°
- **Scale Length** : Approx. 65mm
- **Terminal**:
4mm socket captive head, suitable for wire or pin-type test lead.
- **Material and Color** :
Acrylic resin meter cover, white scale plate, plastic stand in black.
- **Safety Standard** :
IEC/EN 61010-1 CAT II 300V
EN 61326-1 EN 61000-4-2 EN 61000-4-3

Name		Range	No.
AC Ammeter (Rectifier Type) Accuracy: ±2.5% F.S.	1 Range	1A	205ACA 100
		500mA	205ACA 101
		5A	205ACA 102
	2 Ranges	1/10A	205ACA 200
		10/100mA	205ACA 201
		100/500mA	205ACA 202
		500mA/1A	205ACA 203
		80/200mA	205ACA 204
	3 Ranges	50mA/500mA/5A	205ACA 301
		500mA/1A/5A	205ACA 302
		1/2.5/5A	205ACA 303
		5/10/25A	205ACA 304
		30/100/500mA	205ACA 305
AC Voltmeter (Rectifier Type) Accuracy: ±2.5% F.S.	1 Range	5V	205ACV 100
		10V	205ACV 101
		20V	205ACV 102
		50V	205ACV 103
	2 Ranges	250V	205ACV 104
		10/100V	205ACV 201
		3/30V	205ACV 202
	3 Ranges	5/15V	205ACV 203
		15/30/50V	205ACV 301
		30/50/100V	205ACV 302
DC Ammeter (Moving Coil Type) Accuracy: ±2.0% F.S.	1 Range	50μA	205DCA 100
		100μA	205DCA 101
		500μA	205DCA 102
		3mA	205DCA 103
		10mA	205DCA 104
		100mA	205DCA 105
		200mA	205DCA 106
		300mA	205DCA 107
		500mA	205DCA 108
		500μA	205DCA 109
		1A	205DCA 110
		2.5A	205DCA 111
		3A	205DCA 112
		5A	205DCA 113
		10A	205DCA 114
	2 Ranges	1mA	205DCA 115
		1/10mA	205DCA 200
		1/5A	205DCA 201
		1/10A	205DCA 202
		50/500mA	205DCA 203
		50/500μA	205DCA 204
	3 Ranges	50mA/500mA/5A	205DCA 301
		100mA/1A/5A	205DCA 302
		1/5/10A	205DCA 303
		50/500/5000μA	205DCA 304
		100μA/500μA/1mA	205DCA 305

Name	Range		No.
DC Voltmeter (Moving Coil Type) Accuracy: ±2.0% F.S	1 Range	1V	205DCV 101
		3V	205DCV 102
		5V	205DCV 103
		6V	205DCV 104
		10V	205DCV 105
		15V	205DCV 106
		20V	205DCV 107
	2 Ranges	50/500mV	205DCV 200
		1/10V	205DCV 202
		1/5V	205DCV 203
		2/20V	205DCV 204
		3/15V	205DCV 205
		5/10V	205DCV 206
		5/15V	205DCV 207
		10/50V	205DCV 208
		30/60V	205DCV 209
	3 Ranges	3/10/15V	205DCV 303
		3/15/300V	205DCV 304
		3/15/30V	205DCV 305
3/30/300V		205DCV 306	
DC (Galvanometer Type) Accuracy: ±2.0% F.S.		± 0.1mA	205G 100
		± 0.5mA	205G 101
		± 10V	205G 102
		± 1A	205G 103
		± 3.5G	205G 104
		± 3.5mA	205G 105
		± 30G	205G 106
		± 30mA	205G 107
		± 35G	205G 109
		± 35mA	205G 110
		± 50G	205G 111
		± 60uA	205G 112
Custom Accuracy: ±2.0% F.S.		1A-0-5A	205DC 101
		20µA-0-100µA	205DC 102
		20mA-0-100mA	205DC 103
		5V-0-15V	205DC 104
		50mA/500mA/5A	205DC 105
		3/15/300V	205DC 106

Special ranges are available upon request.