



EDAC 222-02

Cost effective monitoring

Monitor two alarm inputs and report directly to the people most capable of correcting the problem.

Control of two appliances via the outputs.

The EDAC222-02 has 2 trigger inputs and 2 controlled outputs plus many additional features. The auto dialler can be set up to monitor security systems, essential equipment and processes. It may be used with any combination of triggers.

Upon the occurrence of an alarm event the EDAC222-02 is triggered and will automatically call the list of pre-programmed telephone numbers, cellular/mobile phone numbers associated with the trigger input.

A user recorded voice message associated with the trigger will then be communicated to the dialled connection.

The EDAC222-02 has the ability to independently control 2 outputs.

This level of functionality and flexibility enables the EDAC222-02 to be a cost-effective platform for essential monitoring and control in a variety of applications. It eliminates the expense of third party

monitoring and enables contact to be made directly with the people that need to be informed.

If you are considering using an alternative to a standard land line we can assist you with both [GSM](#) and [NextG](#) options, compatible with your choice of Autodialler.

Features

- 2 independent trigger inputs
- user recordable 8 second audio message per input and user recordable 4 second site message
- Voice messages held in non volatile memory.
- List of 16 telephone numbers or 4 seperate lists of 4 numbers
- 2 outputs which can be operated remotely
- Full PIN security
- Cost effective
- Direct communication with those who are most capable of solving problems
- Uses existing telephone lines
- Compatible with cellular phones in lieu of standard phone lines
- AUSTEL APPROVED