



Cordless Recipro Saw
DJR183/ DJR185 18V LITHIUM-ION
DJR143/ DJR145 14.4V LITHIUM-ION

Satisfy Professional's Needs



Multi-position switch

enables various grip position for versatile operations.

Trigger switch

Photo : DJR145

Paddle switch

Photo : DJR183

Lightweight Design for Easy Handling

Two switch levers are available with variable speed control.

Multi-position switch to make operation easier at any grip position for versatile applications by pulling either trigger.



Trigger switch



Paddle switch



LED job light
with pre-glow function

Rubberized soft grip



Photo : DJR183



Shoe adjustment
Shoe is adjustable by loosening/fastening a screw for comfortable operation.



DJR143, DJR183
Toolless blade clamp for Recipro saw blade



DJR145, DJR185
Blade clamp compatible with both Recipro and Jig saw blades



Blade can be set in place with a single insert and removed simply by turning the blade clamp.

Low Vibration

Test material: Douglas-fir

DJR183 7.0m/s²

Competitor M 12.5m/s²

Cordless Recipro Saw DJR183/ DJR185/ DJR143/ DJR145

	DJR183/ DJR185 	DJR143/ DJR145 
Capacity	Pipe : 50mm (2") Wood : 50mm (2")	Pipe : 50mm (2") Wood : 50mm (2")
Length of stroke	13mm (1/2")	13mm (1/2")
Strokes per minute (spm)	0-3,000	0-3,000
Dimensions (L x W x H)	392x81x209mm (with BL1815/N) (15-1/2"x3-3/16"x8-1/4")	392x81x201mm (with BL1415) (15-1/2"x3-3/16"x7-7/8")
Net weight*	1.5kg (3.4bs)(with BL1815/N) DJR183 1.6kg (3.4bs)(with BL1815/N) 1.8kg (3.9bs)(with BL1830, BL1840)	1.5kg (3.2bs)(with BL1415) DJR145 1.5kg (3.3bs)(with BL1415) 1.7kg (3.7bs)(with BL1430, BL1440)
 Variable Speed	 Bayonet Shank Jig Saw Blade (DJR185, DJR145 only)	Standard Equipment : Charger, Battery Cartridge, Recipro Saw Blades, Hex Wrench
 Brake	 Carrying Case	
 Built-in Job Light		

*weight according to EPTA-Procedure 01/2003 Items of standard equipment and specifications may vary by country or area.



Jigsaw / Reciprosawing
Accessories

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN BD-BC

Li-ion Battery & Charger Time Reference, Compatibility Chart

18V Lithium-ion		14.4V Lithium-ion		DC18RC  DC18RA 	Four Port Multi Charger DC18SF 	DC18SD  DC18SE (Automotive) 	
5.0 Ah	 BL1850 (196673-6)			45 min. Fast Charging	110min. 1 to 2 batteries 220min. 3 to 4 batteries	110 min.	
4.0 Ah	 BL1840 (196397-4)	 BL1440 (196386-9)		36 min. Fast Charging	90min. 1 to 2 batteries 180min. 3 to 4 batteries	90 min.	
3.0 Ah	 BL1830 (194204-5)	 BL1430 (194065-3) BL1430A (194359-6) with Battery fuel gauge		22 min. Fast Charging	60min. 1 to 2 batteries 120min. 3 to 4 batteries	60 min.	
2.0 Ah	 BL1820 (196462-9)			24 min. Fast Charging	45min. 1 to 2 batteries 90min. 3 to 4 batteries	45 min.	
1.5 Ah	 BL1815N (196449-1)	 BL1415N (196877-0) BL1415NA (196280-5) with Battery fuel gauge		15 min. Fast Charging	30min. 1 to 2 batteries 60min. 3 to 4 batteries	30 min.	
1.3 Ah	 BL1815 (194513-2) For Model: DBN500, DBY180, DCF050, DCF201, DCF300, DCG180, DCJ200, DCL180, DCL182, DDF450, DDF452, DDF453, DDF456, DDF459, DDF480, DFR550, DFR750, DFS450, DFS451, DHP452, DHP453, DHP456, DHP459, DHP480, DJR183, DJR185, DJ5130, DML184, DML185, DML186, DML800, DML801, DML802, DML803, DML805, DMR050, DMR100, DMR101, DMR102, DMR103B, DMR104, DMR105, DSC162, DSC192, DST221, DTD129, DTD141, DTD142, DTD144, DTD145, DTD146, DTD148, DTL061, DTL063, DTM50, DTM51, DTP140, DTP141, DTW251, DTW253, DTW450, DTW451, DTW281, DUB182, DUB183, DUH423, DUH483, DUH523, DUM168, DUR181, DVC350, DVF104, DVF154, DVR850, DVR450, DVR350	 BL1415 (194558-0) For Model: DCF050, DCF201, DCF300, DCG140, DCJ200, DCL140, DCL142, DDF343, DDF445, DFL201RZ, DFL301RZ, DFL402RZ, DFR440, DFR540, DFS440, DHP343, DJR143, DJR145, DML145, DML146, DML184, DML800, DML801, DML802, DML803, DML805, DMR050, DMR100, DMR101, DMR102, DMR103B, DMR104, DMR105, DPT350, DST110, DST220, DTD134, DTD135, DTD137, DTM40, DTM41, DTP131, DTW280, DUB142, DUB143, DUH421, DUH481, DUH521, DUM166, DUR141, DVC340, DVR340, DVR440			15 min. Fast Charging	30 min. 1 to 2 batteries 60 min. 3 to 4 batteries	30 min.