


NON-COTACT INFRARED THERMOMETER

• TG730IR •



TG730IR



**MAX
MIN** **DATA
HOLD**

°C/°F **AUTO
OFF**



- Pocket size for easy carry
- D:S = 9:1
- Measurement Range
 - 33 ~ 500 °C
 - 27 ~ 932 °F
- Circle laser pointer
- One button for easy operation
- HOLD / MIN / MAX readings with back light LCD display

Electrical Specification:

Range	-33 to +500°C(-27 to +932°F)
Resolution	-9.9°C/°F to 99.9°C/°F : 0.1°C/°F Below -10°C/°F or above 100°C/°F : 1°C/°F
Response Time	1 second
Accuracy	±2.0% of reading or ±2.0°C/°F which one is greater
Field of View (D:S)	9:1
Emissivity	0.95 fixed
Battery Life	about 30 hours continuous use
Operation temp. and humidity	0 ~ 50°C; < 90RH%
Storage temp. and humidity	10~40°C; < 65RH%
Battery	1 x AA size
Display	LCD
Dimensions	150(L) x 25(W) x 27(H) mm
Weight	74 grams including battery



CIRCLE LASER
POINTER

COMPACT DESIGN



techgear.com.tw




非接觸式 紅外線測溫儀

• TG730IR •



TG730IR



- 小型便攜式設計
- D:S = 9:1
- 測量範圍
 - 33 ~ 500°C
 - 27 ~ 932°F
- 圓形激光圈指示
- 一鍵操作，簡單方便
- 最大值/最小值及最後數據保持
- 背光式LCD 顯示



技術規格:

測量範圍	-33至 + 500°C (-27至 +932°F)
分辨率	-9.9°C/°F至99.9°C/°F或以下: 0.1°C/°F
	-10°C/°F或以下及100°C/°F或以上: 1°C/°F
響應時間	1秒
測量精度	±2.0%讀數或 ±2.0°C/°F, 選最大值
測量距離和區域比(D:S)	9 : 1
發射率	0.95固定
電池壽命	約30小時連續使用
工作溫度和濕度	0 ~ 50°C; < 90RH%
儲存溫度和濕度	10~ 40°C; < 65RH%
電池	1 x AA Size
顯示器	LCD
外形尺寸	150 (L) × 25 (W) × 27 (H) mm
重量	74克包括電池



圓形激光圈
指示

小巧設計



GEAR TO
TECHNOLOGY



techgear.com.tw

