

CCTV TESTER

• TG261CT •



TG261CT




- Portable 3.5" TFT Color LCD Screen
- Auto NTSC/PAL
- Check Surveillance Camera Video Signal
- Color Bar Video Pattern Signal Generator
- PTZ controller & capture command data from RS485/RS232
- LAN cable Testing
- Audio checking from the microphone
- Rechargeable 1050mAh Li-Polymer battery
- Supply DC12V 1A Power output for camera

Electrical Specification:

Video Test		Video Signal Generation	
Video signal system	NTSC/PAL (Auto detect)	Color bar generation	Output one channel PAL/NTSC color bar video signal for testing monitor or video cable.
LCD	3.5" TFT-LCD, resolution = 960 x 240		
Video parameter	CONTRAST / BRIGHTNESS / COLOR / LANGUAGE / KEY TONE	UTP CABLE TEST	
Video IN/OUT	BNC jack	UTP cable test	Test UTP cable connection status and display in the screen.
Video Output spec	1.0 Vp-p	DC12V 1A power output	
PTZ controller		DC12V power output	Output DC12V1A power for camera
Communication	RS232 / RS485	Audio input test	
PTZ Protocol	Compatible with PELCO-D, PELCO-P, Yaan, Samsung, Lilin, Molyax, Minking, AD, Fastrax, CBC, SONY, LG, DTA, Pearmain, Vicon, Vcltp, DHYCT06, SANYO.	Audio input test	test the pickup and other audio equipments on the front-end
Baud Rate (bps)	300/600/1200/2400/4800/9600/19200	RS485/RS232 data analyst	
		Data Monitor	Captures and analyzes the command data from controlling device
		POWER	
		Power Adapter	DC12V/1A
		Battery	Rechargeable 1050mAh Li-Poly battery



techgear.com.tw



Made in Taiwan